



50 Hz R134a											
4 T condensation	5 T évaporation	(°C)	-25	-20	-15	-10	-5	0	5	10	15
30	1 P frigorigère	(W)	398	533	691	879	1099	1358	1658	2005	2403
	2 P absorbé	(W)	296	327	356	383	412	445	483	529	585
	3 absorbé	(A)	2'37	2.43	2.5	2.59	2.67	2.77	2.87	2.99	3.11
40	1 P frigorigère	(W)		460	607	778	977	1208	1476	1786	2142
	2 P absorbé	(W)		340	378	412	445	479	516	559	609
	3 absorbé	(A)		2.45	2.55	2.66	2.78	2.9	3.03	3.17	3.32
50	1 P frigorigère	(W)			518	672	849	1054	1290	1563	1876
	2 P absorbé	(W)			392	436	477	517	557	601	649
	3 absorbé	(A)			2.59	2.73	2.87	3.03	3.19	3.35	3.53
60	1 P frigorigère	(W)				563	718	896	1101	1336	1607
	2 P absorbé	(W)				452	506	555	603	651	702
	3 absorbé	(A)				2.8	2.97	3.15	3.34	3.53	3.74

Technical Data	1200	1400
Cooling Capacity [L35-L35]	1200W (4093 BTU/h)	1400 W (4775 BTU/h)
Refrigerant Type	R134a	R134a
Thermostat Setting	32°C	32°C
Hysteresis	4°C	4°C
Condenser Fan Flow	530m3/h	530m3/h
Evaporator Fan Flow	950m3/h	950m3/h
Weight	32kgs	32kgs
Dimensions (Width*Height*Depth) mm	393 X 973 X 217	393 X 973 X 217
Operating Temperature	+7,5°C - +55°C	+7,5°C - +55°C
Corrosion Protection		Stainless Steel
Level Implementation	Side Mount	Side Mount
IP Rating	IP 54 / IP 65	IP 54 / IP 65
Frequency	50/60 Hz	50/60 Hz
Power Load	220V- 240V	220V- 240V
Fans	Ebm Papst	Ebm Papst
Compressor	Tecumseh / Embraco	Tecumseh / Embraco