



50 Hz R404A											
4 T Condensation	5 T évaporation	(°C)	-25	-20	-15	-10	-5	0	5	10	15
30	1 P frigorifique	(W)	1332	1754	2237	2793	3431	4162	4997	5945	7017
	2 P absorbéé	(W)	792	884	965	1040	1108	1174	1238	1304	1373
	3 absorbéé	(A)	2.01	2.1	2.10	2.27	2.35	2.43	2.49	2.56	2.61
40	1 P frigorifique	(W)		1386	1821	2309	2861	3487	4199	5005	5917
	2 P absorbéé	(W)		928	1038	1138	1230	1315	1396	1476	1556
	3 absorbéé	(A)		2.15	2.28	2.41	2.53	2.65	2.78	2.87	2.97
50	1 P frigorifique	(W)			1389	1805	2266	2783	3366	4026	4773
	2 P absorbéé	(W)			1087	1221	1343	1456	1562	1663	1762
	3 absorbéé	(A)			2.34	2.51	2.68	2.84	2.99	3.14	3.26
60	1 P frigorifique	(W)				1296	1662	2065	2515	3024	3601
	2 P absorbéé	(W)				1276	1437	1585	1724	1856	1981
	3 absorbéé	(A)				2.58	2.79	3	3.2	3.39	3.58

Technical Data	4000
Cooling Capacity [L35-L35]	4000W (13644 BTU/h)
Refrigerant Type	R134a
Thermostat Setting	32°C
Hysteresis	4°C
Condenser Fan Flow	1150 m³/h
Evaporator Fan Flow	1750 m³/h
Weight	57 kgs
Dimensions (Width*Height*Depth) mm	487 x 1175 x 310
Operating Temperature	+7,5°C - +55°C
Corrosion Protection	Stainles Steel
Level Implementation	Side Mount
IP Rating	IP 54 / IP 65
Frequency	50/60 Hz
Power Load	380 V - 400 V
Fans	Ebm Papst
Compressor	Tecumseh / Embraco